(Page 1 of 3)

State of California AIR RESOURCES BOARD

EXECUTIVE ORDER A-6-971 Relating to Certification of New Motor Vehicles

GENERAL MOTORS CORPORATION

Pursuant to the authority vested in the Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapter 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below:

Model Year: 2001

Vehicle Type: Passenger Car

Exhaust Emission Standard Category: Low-Emission Vehicle (LEV)

Fuel Type: Gasoline

Test Group: 1GMXV03.0061

Engine Displacement: 3.0 Liters

Evaporative Family: 1GMXR0124919

Special Features and Exhaust Emission Control Systems (ECS): ECS II

ECS I

Sequential Multiport Fuel Injection Three Way Catalytic Converter Dual Heated Oxygen Sensors (two) Exhaust Gas Recirculation

Dual Warm Up Three Way Catalytic Converters

Models Covered:

ECS I: Saturn LS, LW ECS II: Cadillac Catera Sequential Multiport Fuel Injection Dual Three Way Catalytic Converters Dual Heated Oxygen Sensors (two)

Secondary Air Injection

The exhaust certification emission levels and standards, in grams per mile, of nonmethane organic gases (NMOG), carbon monoxide (CO), oxides of nitrogen (NOx), and formaldehyde (HCHO) for the listed vehicle models are as follows. The NMOG exhaust certification emission levels include application of the reactivity adjustment factor (RAF) as specified.

The evaporative hydrocarbon (HC) certification emission levels and standards for three-day diurnal plus hot soak (3D) and two-day diurnal plus hot soak (2D) in grams per test, running loss (RL) in grams per mile, and onboard refueling vapor recovery (ORVR) in grams per gallon of fuel dispensed, for the listed vehicle models are as follows.

UST @ NMOG RA	E 0.04		
NMOG NMOG CO CO NOx NOx NOx (highway) NOx (highway) HCHO HCHO HCHO CO (20°F) NMOG (50°F)	ge 50,000 100,000 50,000 100,000 50,000 100,000 50,000 100,000 50,000 4,000	0.069 (projected) 0.044 0.060 0.9 1.4 0.1 0.1 0.1 0.1 0.002 0.003 5.9 n/a	0.070 0.075 0.090 3.4 4.2 0.2 0.3 0.4 0.015 0.018 10.0 0.150 3.4
NOx (50°F) HCHO (50°F) PORATIVE HC-2D HC-3D HC-RL	4,000 4,000 100,000 100,000 100,000	n/a n/a 1.8 0.7 0.00	0.2 0.030 2.5 2.0 0.05 0.20
	NMOG NMOG CO CO NOx NOx NOx NOx (highway) NOx (highway) HCHO HCHO CO (20°F) NMOG (50°F) CO (50°F) NOx (50°F) HCHO (50°F) HCHO (50°F) HCHO (50°F)	NMOG 100,000 CO 50,000 CO 100,000 NOx 50,000 NOx 100,000 NOx (highway) 50,000 NOx (highway) 100,000 HCHO 50,000 HCHO 100,000 CO (20°F) 50,000 NMOG (50°F) 4,000 CO (50°F) 4,000 NOx (50°F) 4,000 HCHO (50°F) 4,000 HCHO (50°F) 100,000 HC-3D 100,000 HC-3D 100,000 HC-RL 100,000	NMOG 50,000 0.044 NMOG 100,000 0.060 CO 50,000 0.9 CO 100,000 1.4 NOx 50,000 0.1 NOx 100,000 0.1 NOx (highway) 50,000 0.1 NOx (highway) 100,000 0.1 HCHO 50,000 0.002 HCHO 100,000 0.003 CO (20°F) 50,000 5.9 NMOG (50°F) 4,000 n/a CO (50°F) 4,000 n/a NOx (50°F) 4,000 n/a HCHO (50°F) 4,000 n/a PORATIVE HC-2D 100,000 1.8 HC-3D 100,000 0.00 HC-RL 100,000 0.000

BE IT FURTHER RESOLVED: That any debit in the manufacturer's NMOG fleet average compliance plan shall be equalized as required by the "California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles."

BE IT FURTHER RESOLVED: That the 50° Fahrenheit testing requirement for the listed vehicle models has been met based on the compliance plan submitted by the manufacturer in lieu of actual testing.

BE IT FURTHER RESOLVED: That the manufacturer is certifying the listed vehicle models with a partially complying on-board diagnostic system for the aforementioned model year pursuant to Title 13, California Code of Regulations, Section 1968.1(m)(6.2) ("Malfunction and Diagnostic System Requirements--1994 and Subsequent Model-Year Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles and Engines").

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with the following California emission regulations and requirements. Vehicles certified under this Executive Order shall conform to all applicable California emission regulations and requirements.

- Specifications for Fill Pipes and Openings of Motor Vehicle Fuel Tanks (Title 13, California Code of Regulations, Section 2235)
- Motor Vehicle Emission Control and Smog Index Label Specifications (Title 13, California Code of Regulations, Section 1965)
- Emission Control System Warranty (Title 13, California Code of Regulations, Sections 2035 et seq.)
- High-Altitude Requirements and California Inspection and Maintenance Emission Standards (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles)

The Bureau of Automotive Repair will be notified by copy of this order.

Executed at El Monte, California this ______ day of May 2000.

R. B. Summerfield, Chief

Mobile Source Operations Division